Google   generating target geometric model server processor client

Web Show options...   Results **1** - **10** of about **8,490** for **generating targ**

Tip: Save time by hitting the return key instead of clicking on "search"

Computational **geometry** system, interrupt interface, and method ...
A computational **geometry** system, comprising: a **client/server** environment; .... The
method of claim 27 wherein **generating** the **target geometric model** comprises ... data
processor and drawing method with employment of the same ...
www.patentstorm.us/patents/7203634/claims.html

> **Geometric model** comparator and method - US Patent 7149677 Description
> The processing circuitry is configured to **generate a target model** from a source 1,
> system 12 is implemented across a **client/server** network 13 having a ...
> www.patentstorm.us/patents/7149677/description.html

> Show more results from www.patentstorm.us

[ps] DAD – Distributed Adamo Database system at Hermes W. Wander, M. D ...
File Format: Adobe PostScript - View as HTML
from a polarised internal gas **target**. As HERMES-software is relies on the ADAMO ...
Server. Figure 1: A simple **client server model** for DAD. ... DAD provides easy calls to
access and **generate** data sets with a limited. validity period. ... **Processor**. **Server**.
Slowcontrol. Calibration. **Server**. **Geometry**. **Server**. Mapping ...
www.hep.net/chep95/papers/p14/p14.ps
by U Erlangen-Nurmberg - Related articles - All 7 versions

Patents in Class 703/22
A method and apparatus for **generating** a covering set of test cases from ... a **client**
terminal, a connection **server**, a virtual production line, and a real production line. ...
including simulating a **target processor** using binary translation ... of the **geometric model**
(e.g., a CAD **model**) of a multi-component assembly ...
www.freepatentsonline.com/CCL-703-22-p9.html

Vertex Buffer Objects (VBOs)
The testing files (viewsets) within SPECviewperf **generate** OpenGL command streams ...
applications send all the **geometric** data to the graphics **processor** (GPU) every ... bind
operation turns a **client**-state function into a **server**-state function. ... VBOs are intended to
work with the following OpenGL **target** objects: ...
spec.ir.miami.edu/gwpg/gpc.static/vbo_whitepaper.html - Cached

ARTE - An Adaptive Rendering and Transmission Environment for 3D ...
components and we use a transcoding engine to **generate** different modalities for each
component ... When a **client** makes a request for a 3D **model** to a **server**, it first receives
meta-data information .... tem, which supplies a larger portion of the **model geometry** ... 1)
for a **target** frame rate of 15 fps and two models ...
portal.acm.org/ft_gateway.cfm?id=376299&type=pdf - Similar
by IM Martin - 2000 - Cited by 13 - Related articles

An XML Based Component **Model** for **Generating** Scientific ...
onto single or multiple **processor** machines. .... An XML Based Component **Model**. 219.
<script>. <call-method **target**="DA01" name="bayesian">. </script> ... atomic interactions

by using a link-cell (**geometric** hashing) algorithm where all **....** **client**-**server** interaction, delegating this task to the underlying ORB. **...**
www.springerlink.com/index/c7y6qyvg6lp4udra.pdf - Similar
by OF Rana - 2000 - Cited by 18 - Related articles

[PDF] DAD – Distributed Adamo Database system at Hermes W. Wander, M **...**
File Format: PDF/Adobe Acrobat - Quick View
from a polarised internal gas **target**. As HERMES-software is relies on the ADAMO2 entity **...** 2 The **Client Server Model**. As our software development profits from the **...** DAD provides easy calls to access and **generate** data sets with a limited **...** **Processor**. **Server**. Slowcontrol. Calibration. **Server**. **Geometry**. **Server ...**
citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.52.7781&rep...
by U Erlangen-Nurnberg - Related articles

Parallelization of Radiance For Real Time Interactive Lighting **...**
lighting visualization in real time by **generating** more than **....** approach [8] since Radiance requires a **geometric model ...** of data communicated between the **client** and **server**. The **...** **processor** on the **client** side in order to achieve 10 frames **....** Our current results are not yet in the **target** interactive **...**
doi.ieeecomputersociety.org/10.1109/SC.1999.10017
by D Robertson - All 4 versions

Vertex Buffer Objects (VBOs)
The testing files (viewsets) within SPECviewperf **generate** OpenGL command **...** If **geometric** data does not change frequently, however, immediate mode **...** As a result, the bind operation turns a **client**-state function into a **server**-state function. **...** VBOs are intended to work with the following OpenGL **target** objects: **...**
www.spec.org/gwpg/pastissues/Sep1_05/opc.../vbo_whitepaper.html - Cached

1 2 3 4 5 6 7 8 9 10   Next

generating target geometric model server processor clien

Search within results - Language Tools - Search Help - Dissatisfied? Help us im

Google Home - Advertising Programs - Business Solutions - Priva